

# **SILAGE COVERS**

*Quality covers  
that protect  
your silage for  
up to two years*



**Innovators In Agricultural Technology**



**Triple layer for strength and air tight seal**

Black and white layers  
Keeps your silage cool

**High oxygen barrier**

Keeps air out, seals pit, better quality silage

**150 micron thickness with high tensile strength**

Will not puncture when walked on, resists vermin damage

**UV rated for up to 2 years protection of your silage**

Longer if used with Zill 240 Silage Protection Covers

**Quality manufacture - specially made for silage**

**Using Silage covers**

Ensure silage is properly compacted to remove as much air as possible prior to covering.

Cover silage as soon as possible after compaction. Ensure sufficient overlap for each cover, and weigh down with tyres, or bags.

Seal edges to ensure air-tight seal and ensure that water can not enter the stack or pit.

<i>Width</i>	<i>Length</i>	<i>Colour</i>	<i>Thickness</i>	<i>UV</i>
12m	50m	Black/White	150um	2 years
15m	50m	Black/White	150um	2 years
15m	300m	Black/White	150um	2 years
18m	50m	Black/White	150um	2 years
18m	300m	Black/White	150um	2 years



Head Office. 10 Bult Drive,  
Brendale, QLD, 4500, Australia  
Tel. 1300 669 556  
Fax: 07 3205 4327  
Email. [admin@grevilliaag.com.au](mailto:admin@grevilliaag.com.au)  
Web. [grevilliaag.com.au](http://grevilliaag.com.au)